



ATTACHMENT DETAIL

1. SILICONE IS TO BE PLACED ON THE BLIND STOP AND TRIM STOP SO THAT IT ESTABLISHES A SEAL BETWEEN THE FRAME AND BOTH STOPS. A TRIPLE SEAL IS FORMED BY CONTACT BETWEEN THE FRAME AT THE BLIND STOP, TRIM STOP AND COMPRESSIBLE SEAL.
2. THE NORMAL INSTALLATION WILL INCLUDE FACTORY, PRE-DRILLED HOLES IN THE FRAME THAT ATTACH PERPENDICULAR TO THE FRAME INTO THE EXISTING INTERIOR JAMB (TYPICALLY PIERCING THE COMPRESSIBLE SEAL AT THAT POINT).
3. FACTORY SUPPLIED ATTACHMENT SCREWS (#6A x 1 1/2" pan head) SHOULD BE USED TO ATTACH THE FRAME TO THE JAMB.
4. THE TRIM STOP AND TRIM (QUARTER ROUND) COMPLETE THE INTERIOR INSTALLATION. THE USE OF A QUARTER ROUND (AS SHOWN) OR OTHER DECORATIVE TRIM IS BASED ON CUSTOMER PREFERENCE. THE 1/2 X 1/2 TRIM STOP IS SUFFICIENT FOR SEALING PURPOSES, THOUGH DECORATIVE FINISH TRIM DOES MAKE FOR NICE DETAIL.

QUANTAPANEL®
 602-PW INSULATING GLASS SYSTEM
 DETAIL - INSTALLED

NOTES:

DATE	06/16/2020
SCALE	1" = 5'
DRAWN BY	R.A.S.